

KARI 5 transport bag, 5L, WLL 5kg

B05

Personal Kit and Tool Bag for attaching to harness belt. 5kg WLL

Features:

- Welded seams for increased strength
- Double thickness base for increased durability
- Waterproof construction
- Meets requirements of IPX7 (accidental submersion in water)
- Lockable for issuing personal or rescue equipment
- Rated for lifting up to 5kg
- Factor of safety 7:1
- External daisy chain for extra storage (rated 5kg)
- Daisy chain rated for tool lanyards: 0.5kg x 2m
- Marked with WLL & unique ID number for control as lifting accessory
- 2 D-rings for attachment to harness

Design and construction ensures a long working life even in harsh or aggressive environments.

Waterproof when the top is rolled down with 3 turns and the side straps are closed. Tested to the requirements of IPX7 - the contents will stay dry if the bag is accidentally submerged under water.

2 D-rings either side of each closing buckle allow the bag to be 'locked' with a cable tie or tamper evident tag.

Rated with WLL and 7:1 factor of safety. WLL includes any items attached to tool loops or daisy chains. Tool tether rating includes allowance for the higher load generated with a falling tool e.g. 5kg can be suspended from the daisy chain or a 0.5kg tool can be dropped 2m onto it.

Attachment D-rings are large enough to accommodate a karabiner so that the bag can be attached to the harness via gear loops or directly around the belt.

Rolling the top of the bag down by 1 turn holds it open to allow easy access when working.



Specifications:

NB: specifications and colour may change without notice.

Size: 5L

EN Test Mass: Non PPE

Loading: 5kg WLL

Conformity: Non PPE

Materials: PVC, Nylon

Weight (kg): 0.35

Industries: All work at height markets

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

PDS22

10/02/22